

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (Cancelled)
2. (Currently Amended) ~~The method of claim 1~~ A method for detecting defects in a test specimen, the method comprising:
applying a liquid detection medium to the test specimen;
exciting the test specimen to cause the liquid detection medium to produce a defect signature for a defect in the test specimen; and
monitoring the liquid detection medium for defect signatures produced by the liquid detection medium, said monitoring including monitoring the liquid detection medium to detect a temperature differential indicative of a defect in the test specimen,
wherein:
the defect signature comprises a cold signature; and
the monitoring comprises thermally monitoring the liquid detection medium to detect cold signatures.
3. (Original) The method of claim 2, wherein the excitation of the test specimen causes liquid detection medium to be ejected from the test specimen at about the defect, the ejected liquid detection medium cooling by evaporation and producing the cold signature.
4. (Original) The method of claim 2, wherein the thermally monitoring comprises acquiring infrared images of the liquid detection medium.

5. (Original) The method of claim 4, wherein the acquiring comprises:
acquiring an infrared image of the liquid detection medium before excitation;
acquiring one or more infrared images of the liquid detection medium during excitation; and
subtracting from the infrared image acquired before excitation the one or more infrared images acquired during excitation.
6. (Currently Amended) The method of claim 2 ~~[[1]]~~, wherein the defect signature further comprises a vibrational mode pattern.
7. (Original) The method of claim 6, wherein the vibrational mode pattern comprises a standing wave of liquid detection medium on the test specimen generally above the defect.
8. (Original) The method of claim 6, wherein the vibrational mode pattern comprises an ejection of liquid detection medium from the test specimen at about the defect.
9. (Previously Presented) The method of claim 8, wherein the monitoring comprises visually monitoring the liquid detection medium to detect the ejection of liquid detection medium from the test specimen.
10. (Original) The method of claim 9, wherein the visually monitoring comprises acquiring real-time images of the liquid detection medium.
11. (Original) The method of claim 10, further comprising displaying the real-time images to an inspector.
12. (Currently Amended) The method of claim 2 ~~[[1]]~~, wherein the applying comprises misting water on the test specimen.

13. (Currently Amended) The method of claim 2 ~~[[1]]~~, wherein the exciting comprises ultrasonically exciting the test specimen.

14. (Currently Amended) The method of claim 2 ~~[[1]]~~, wherein the test specimen comprises a composite structure.

15. (Currently Amended) The method of claim 2 ~~[[1]]~~, wherein the liquid detection medium includes insoluble particles which form a visible pattern on the test specimen at about a defect after the excitation.

16. (Cancelled)

17. (Currently Amended) ~~The method of claim 16~~ A method of detecting defects in a test specimen without having to rely on heating of the test specimen, the method comprising:

applying a liquid couplant to at least a first surface portion of the test specimen;

acoustically exciting the test specimen; and

monitoring the liquid couplant for vibration effects which indicate defects in the test specimen, the vibration effects including an ejection of liquid couplant from the first surface portion, wherein the monitoring comprises thermally monitoring the liquid couplant for a cold signature.

18. (Original) The method of claim 17, wherein the excitation of the test specimen causes liquid couplant to be ejected from the first surface portion at about a defect, the ejected liquid couplant cooling by evaporation and producing the cold signature.

19. (Original) The method of claim 17, wherein the thermally monitoring comprises acquiring infrared images of the liquid couplant.

20. (Currently Amended) The method of claim 17 ~~[[16]]~~, wherein the monitoring comprises visually monitoring the liquid couplant to detect the vibration effects.

21. (Original) The method of claim 20, wherein the visually monitoring comprises acquiring real-time images of the liquid couplant.

22. (Original) The method of claim 21, further comprising displaying the real-time images to an inspector.

23. (Currently Amended) The method of claim 17 ~~[[16]]~~, wherein the applying comprises misting water on the first surface portion.

24. (Currently Amended) The method of claim 17 ~~[[16]]~~, wherein the acoustically exciting comprises ultrasonically exciting the test specimen.

25. (Original) A method of detecting defects in a test specimen, the method comprising:

applying a liquid couplant to at least a first surface portion of the test specimen;

acoustically exciting the test specimen to cause an ejection of liquid from the first surface portion at about a defect in the test specimen, the ejected liquid cooling by evaporation and producing a cold signature for said defect; and

thermally monitoring the liquid couplant to detect cold signatures produced by the liquid couplant.

26. (Original) The method of claim 25, wherein the thermally monitoring comprising acquiring and analyzing infrared images of the liquid couplant.

27. (Original) The method of claim 25, wherein the thermally monitoring comprises acquiring real-time infrared images of the liquid couplant and displaying the real-time infrared images to an inspector.

28. (Original) The method of claim 27, wherein the acquiring comprises:
acquiring an infrared image of the liquid couplant before excitation;
acquiring one or more infrared images of the liquid couplant during excitation; and
subtracting from the infrared image acquired before excitation the one or more infrared images acquired during excitation.

29. (Cancelled)

30. (Cancelled)

31. (Currently Amended) The system of claim 32 ~~[[30]]~~, further comprising a display device for displaying the images to an inspector.

32. (Currently Amended) ~~The system of claim 30, wherein~~ A system for detecting defects in a test specimen without having to rely on heating of the test specimen, the system comprising:

a liquid couplant on the test specimen;

an exciter coupled to the test specimen to excite the test specimen to cause the liquid couplant to produce a defect signature for a defect in the test specimen; and

a device to detect defect signatures produced by the liquid couplant in response to the excitation including at least one of an ejection of liquid couplant from the test specimen and a temperature differential indicative of a defect in the test specimen, the device comprising a camera for acquiring images of the defect signatures, wherein the camera comprises an infrared camera for acquiring

infrared images of cold signatures produced by the liquid couplant in response to the acoustic excitation.

33. (Currently Amended) The system of claim 32 ~~[[29]]~~, wherein the exciter comprises an ultrasonic welder.

34. (Cancelled)

35. (Cancelled)